



# Mud-Sucker® Honey Wagon Pump Out

## MODEL: 2FA-EC-T-300G

*Trailer Mounted*

The Mud-Sucker Honey wagon Series is designed to pumping any type of non-explosive liquid or oil, including raw sewage, debris-laden water, and marine bilge wastewater.



### PERFORMANCE RANGE

MAX. CAPACITY	25 GPM
MAX. SUCTION LIFT	20' Vertical or 75" Horizontal
MAX. DISCHARGE HEAD	50' Vertical or 300' Horizontal
SOLIDS HANDLING	1.5" Dia. or 50% by volume

### PUMP & MOTOR SPECIFICATIONS

SUCTION INLET SIZE	2"
DISCHARGE OUTLET SIZE	2"
MAX. LIQUID TEMPERATURE	140°F (60°C) Continuous
RPM SPEED OF DIAPHRAGM	59
PUMP BODY CASING	Marine Grade Aluminum (ASTM A356, Class 30)
DIAPHRAGM	7" Dia Fabric Reinforced Buna-N
FLAPPER VALVES	Fabric Reinforced Buna-N
GEARBOX	SEW Eurodrive Model R37 Cast Iron housing with heat treated gears
HARDWARE	Stainless Steel 316
ROD END BEARING	
<i>Body:</i>	- Carbon steel, protective coated for corrosion resistance.
<i>Ball Bearing:</i>	- Sintered steel, heat treated, oil impregnated.
Ultimate Radial Static Load Capacity	- 9,000 Lbs
Approx Dimensions of Honey wagon System	128" x 64" x 60" (LxWxH)
MOTOR SPECIFICATION	<i>Horsepower: 1 Speed: 1800 RPM</i> <i>Power Supply: Three-Phase; 60 Hz; , 230/460V (Max Full Load Amp 1.4)</i> <i>Enclosure: TEFC Duty: Continuous; Ambient Temp: 104°F (40°C)</i>

### TRAILER UNIT

Discharge Hose:	2" x 40' Suction Hose (Hi-Strength Tiger Tail Hose with Cam-Locks with holder)
Suction Hose:	2" x 4' Discharge Layflat Hose into Tank
R.V Adapter:	Universal 3" Fitting to RV with 1-1/2" Ball Valve and Clear Swing Check Valve
Tank:	300 US Gallon Polyethylene Tank with vent, bulk head fitting and discharge drain valve.
Trailer:	Single Axle Fabricated Steel with 2" Ball Hitch, Chain, Utility Jack, Fenders with step deck, Steel Tank Cradle, 3,500 lbs leaf spring suspension with ST205/75D14 Tires

**Customer Service North America: 1-888-829-2783 • Fax: 1-888-883-3320**  
**• E-mail: [info@wastecorp.com](mailto:info@wastecorp.com) • International: (201) 445-2882**